

Product data sheet Characteristics

2025S-WE SWITCHED SOCKET TWIN 10A 250V **SHUTTER**





Main Range of product Series 2000 Product or component Switched socket type Product brand Clipsal Colour White electric

Complementary

Control type ON/OFF button Number of gangs 2 gangs Pin number 3 Number of power socket outlets 2 Actuator Switch Rocker Mounting position Horizontal Fixing mode By screws Local signalling Without light indicator Material Plastic Surface finish Glossy [Ue] rated operational voltage 250 V AC [In] rated current 10 A Depth 28 mm Length 116 mm Width 76 mm Fixing center 84 mm		
Pin number 3 Number of power socket outlets 2 Actuator Switch Rocker Mounting position Horizontal Fixing mode By screws Local signalling Without light indicator Material Plastic Surface finish Glossy [Ue] rated operational voltage 250 V AC [In] rated current 10 A Depth 28 mm Length 116 mm Width 76 mm	Control type	ON/OFF button
Number of power socket outlets 2 Actuator Switch Rocker Mounting position Horizontal Fixing mode By screws Local signalling Without light indicator Material Plastic Surface finish Glossy [Ue] rated operational voltage 250 V AC [In] rated current 10 A Depth 28 mm Length 116 mm Width 76 mm	Number of gangs	2 gangs
Actuator Switch Rocker Mounting position Horizontal Fixing mode By screws Local signalling Without light indicator Material Plastic Surface finish Glossy [Ue] rated operational voltage 250 V AC [In] rated current 10 A Depth 28 mm Length 116 mm Width 76 mm	Pin number	3
RockerMounting positionHorizontalFixing modeBy screwsLocal signallingWithout light indicatorMaterialPlasticSurface finishGlossy[Ue] rated operational voltage250 V AC[In] rated current10 ADepth28 mmLength116 mmWidth76 mm	Number of power socket outlets	2
Fixing mode By screws Local signalling Without light indicator Material Plastic Surface finish Glossy [Ue] rated operational voltage 250 V AC [In] rated current 10 A Depth 28 mm Length 116 mm Width 76 mm	Actuator	
Local signalling Material Plastic Surface finish Glossy [Ue] rated operational voltage [In] rated current Depth 28 mm Length 116 mm Width Width Width Without light indicator Without light indicator Blossy Lossy Glossy 10 A 250 V AC 110 A 116 mm	Mounting position	Horizontal
Material Plastic Surface finish Glossy [Ue] rated operational voltage 250 V AC [In] rated current 10 A Depth 28 mm Length 116 mm Width 76 mm	Fixing mode	By screws
Surface finish Glossy [Ue] rated operational voltage 250 V AC [In] rated current 10 A Depth 28 mm Length 116 mm Width 76 mm	Local signalling	Without light indicator
[Ue] rated operational voltage 250 V AC [In] rated current 10 A Depth 28 mm Length 116 mm Width 76 mm	Material	Plastic
[In] rated current 10 A Depth 28 mm Length 116 mm Width 76 mm	Surface finish	Glossy
Depth 28 mm Length 116 mm Width 76 mm	[Ue] rated operational voltage	250 V AC
Length116 mmWidth76 mm	[In] rated current	10 A
Width 76 mm	Depth	28 mm
	Length	116 mm
Fixing center 84 mm	Width	76 mm
	Fixing center	84 mm

Environment

Standards	AS/NZS 3100	
	AS/NZS 3112	
	AS/NZS 3133:approval number S/1	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	115 g	
Package 1 Height	26 mm	
Package 1 width	115 mm	
Package 1 Length	75 mm	
Unit Type of Package 2	BB1	
Number of Units in Package 2	10	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or intellability of these products for specific user applications. It is the douwn party such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Package 2 Weight	1.15 kg
Package 2 Height	122 mm
Package 2 width	141 mm
Package 2 Length	161 mm
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Weight	11.5 kg
Package 3 Height	254 mm
Package 3 width	348 mm
Package 3 Length	445 mm

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

Life Is On