

Product data sheet Characteristics

1043PA-ZB

Switch, Clipsal Solis, 3 gangs, horizontal, 16AX/20A, matt black



Main	
Range	Clipsal Solis
Product brand	Clipsal
Product or component type	Switch
Assembly Type	Complete product
Outlet standard deviation	Australian/New Zealand
Colour tint	Matt black

Complementary

- Compression y	
Number of gangs	3 gangs
[Ue] rated operational voltage	230/240 V
Network type	AC
Network frequency	50 Hz
Rated current	20 A/16 AX
Control type	Push-button
Connections - terminals	Screw terminals
Installation Type	Flush
Number Of Switches	3
Material	Plastic
Installation direction	Horizontal
Surface treatment	Painted
Load type	LEDi lamp 0250 W 20 A/16 AX
Terminals Capacity	4 x 1.53 x 2.5 mm²
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Wire stripping length	10 mm
Mounting Type	Screw
Cover Thickness	4.5 mm
Mounting Centers	84 mm
Cut-out dimensions	93 x 50 mm
Product certifications	RCM
Surface finish	Matt
Height	74 mm
Width	148 mm
Depth	45.5 mm
Embedding depth	41 mm
Motor M-rating AS3133	M80
Switch function	1-pole 1/2-way

Environment

Ambient air temperature for operation	045 °C
Relative humidity	1095 %
Standards	AS/NZS 60669

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	☐ China RoHS Declaration	
RoHS exemption information	₫Yes	

