

Product data sheet Characteristics

40PWSA-LB

deviation

Push button adaptor, Clipsal Solis T Series, for wiser socket, living brass



Main Range Clipsal Solis T Series Product or component type Adaptor Outlet standard Australian/New Zealand

Complementary

Control type ixing mode Colour tint	Push-button Screw Living brass Horizontal
	Living brass
Colour tint	
	Harizontal
nstallation direction	Honzontal
Surface finish	Matt
Surface treatment	Painted
lumber Of Switches	1
Naterial	Brass
leight	51 mm
Vidth	22 mm
Pepth	30 mm
Product certifications	RCM

Environment

Ambient air temperature for operation	045 °C
Relative humidity	1095 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or intelability of these products for specific user applications. It is the douty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.