



## 10 M Surface mounting enclosure IC2 EGY

VD110PT

### Architecture

Fixing mode	surface-mounting
-------------	------------------

### Functions

With a pipe-in lead	yes
---------------------	-----

### Compatibility

Compatible with DIN rail mounting	yes
-----------------------------------	-----

### Main electrical features

Nominal voltage	400 V
-----------------	-------

### Electric current

Rated current	63 A
---------------	------

### Cover, door

Type of door closing	Latch
Identification od protection index	40
Interlockable	no
Cover type	Closed (plain)
Door locking	without
Door leave	single
Door quantity	1
Cover type	Door
Transparent cover or door	no

### Materials

Colour	pure white
Colour	white
RAL colour	RAL 9010 - Pure white
Material	plastic
Type of surface treatment	untreated

#### Dimensions

Depth of installed product	91 mm
Internal depth	72 mm
Height of installed product	170 mm
Width of installed product	206,5 mm
Width in division units	10

#### Installation, mounting

Suitable for outdoor use	no
--------------------------	----

#### Accessories included

Mounting plate included	no
With lock	no

#### Equipment

Number of rows	1
Quantity of section in width	1
Quantity of rails	1
Can be accessorized	yes
Extension possible	no

#### Standards

GWT Glow wire test	650 °C
European directive WEEE	not concerned

#### Safety

IK protection code against mechanical impacts	IK07
Protection index IP	IP40
Protection class	isol.class II
Halogen free	yes
Ultraviolet resistant	no

#### Use conditions

Operating temperature	-25 40 °C
-----------------------	-----------