



SPECIFICATIONS

DIMENSIONS	R951 (Standard): L80 x W40 x D31mm R952 (Flush): L73 x W40 x D31mm
CUT OUT	70 x 35mm Cut holes with extra caution (5mm rim)
COLOUR TEMP	3000K Warm White
CRI	90
LIFESPAN	50,000 hours (L70)
BEAM ANGLE	45°
MATERIAL	Aluminium
IP RATING	IP40
CLASSIFICATION	IC-F Rated
DRIVER	Sold separately 350mA
WARRANTY	5 Year Warranty

INSTALLATION NOTES

R952 is designed to be installed at ground level as pictured. Bottom of the fitting must sit directly on the floor surface with zero gap for desired light effect.

50
LUMENS1.05
WATTS350_{mA}
SERIES

Driver sold separately, specify when ordering.

AVAILABLE IN

DESCRIPTION	CODE
White 3000K (Standard)	R951 W3
Black 3000K (Standard)	R951 B3
White 3000K (Flush)	R952 W3
Black 3000K (Flush)	R952 B3

IMPORTANT:

1. Connection to live driver will permanently damage all lighting on circuit. Halcyon takes no responsibility for product failures from incorrect wiring.
2. Constant current LED fittings must be wired in series ensuring correct polarity. Incorrect polarity / wiring will cause permanent LED and/or driver failure.
3. Pulsing/flashing lighting indicates wiring fault or under/overloaded driver power off immediately.