

Control Cables

CU CNTRL 1.5 X 19

Contact

Sales and Customer Solutions
Phone: 0800 639 267
sales.nz@nexans.com

Nexans Ref.: APAQ05AA019CXWW

Country Ref.: 3593

Cu conductors, PVC insulation (numbered cores), Laid up, Black PVC sheath. 450/750 V. Made to AS/NZS 5000.3,

DESCRIPTION

Application

- Industrial and commercial applications
- Used as a connections type of cable between control cabinets where a number of control signals are required; or for use in any areas where control of equipment is required.
- Both unarmoured and armoured controls are used in a similar style of application, the only difference being that in the case of unarmoured cable the customer may require mechanical protection of the cable.



STANDARDS

National AS/NZS 5000.3

CHARACTERISTICS

Construction characteristics

Conductor material	Copper
Insulation	PVC
Outer sheath	PVC
Core identification	Black numbers

Dimensional characteristics

Number of cores	19
Conductor cross-section	1.5 mm ²
Nominal overall diameter	18.1 mm
Gland Size (A2 or A2F)	25
Approximate weight	0.56 kg/m

Electrical characteristics









Max. DC resistance of the conductor at 20°C	13.6 Ohm/km
Rated Voltage U ₀ /U	450/750 V

Usage characteristics

Max. conductor temperature in service	75 °C
---------------------------------------	-------

CURRENT CARRYING CAPACITIES (IN AMPS) - CONTROL CABLES

Control cables

Conductor cross-section [mm²]	 Cu	 Cu	 Cu	 Cu
1.5	21	33	17	28.6
 Unenclosed touching 2 cond.	 Voltage Drop 2 Cond. Single Phase (mV/A.m)		 Unenclosed touching 3 cond.	
 Voltage Drop 3 Cond. Three phase (mV/A.m)				

Note

- Content from AS/NZS 3008.1.2:2010 has been reproduced with the permission from Standards New Zealand under Copyright Licence 000926. Please see the Standard for full details.
- The values in this table are for typical New Zealand installation conditions of:
Ambient Air Temperature 30°C