

# Product data sheet Characteristics

# PDL319MAC-TN adaptor RJ SystimaxaT&T, 10Pk



ic
ket

#### Complementary

Complementary		
Device mounting	Flush	
Data socket type	RJ45 - 1 contacts	
Number of gangs	16 gangs	
Number of modules	1 module 23 x 23 x 12 mm	
Fixing mode	Clip-in	
Type of footprint	Systimax AT&T	
Colour tint	Translucent (TN)	
Surface finish	Glossy	
Type of packing	Polybag	
Quantity per set	Set of 10	
Sale per indivisible quantity	1	
Material	ABS + PC: adaptor	
Net weight	0.017 kg	

## **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	19.1 g	
Package 1 Height	12 mm	
Package 1 width	23 mm	
Package 1 Length	23 mm	

## Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.