

Product data sheet Characteristics

PDL394G

PDL Iconic, switched socket, switch & socket, horiz, 10 A





Main	
Range	PDL Iconic
Product or component type	Switched socket
Device presentation	Mechanism with fixing frame
Outlet poles configuration	2P + E with shutter
Outlet standard	Australian

Complementary

Device mounting	Flush
Number of power socket outlets	1
Number of rocker	1
Range compatibility	socket-outlet
Outlet standard description	With earthing contact
Outlet standard	Australian/New Zealand
Ground lug position	Straight 180° position
Fixing mode	By screw
Installation direction	Horizontal
Colour	Vivid white (VW)
Type of packing	Polybag
Quantity per set	Set of 10
Sale per indivisible quantity	1
Rated current	10 A at 250 V AC 50 Hz
Electrical durability	12000 cycles
Connections - terminals	3 screw terminals
Screwdriver shape	Philips No 2
	Square drive no 1 (SQ1)
Clamping connection capacity	1 x 2.54 x 2.5 mm² for rigid cable(s) 1 x 2.54 x 2.5 mm² for stranded cable(s)
	1 x 2.54 x 2.5 mm² for flexible cable(s)
Wire stripping length	16 mm
Material	PC (polycarbonate): fixing frame
	PP (polypropylene): flaps
	POM (polyoxymethylene): shutter
Height	71 mm
Width	115 mm
Depth	31 mm
Embedding depth	24 mm
Net weight	0.096 kg



Environment

Ambient air temperature for operation	045 °C
Relative humidity	1095 %
Standards	AS/NZS 3112
Product certifications	RCM

Packing Units

Package 1 Weight	62.000 g	
Package 1 Height	32.000 mm	
Package 1 width	66.000 mm	
Package 1 Length	62.000 mm	

Offer Sustainability

•		
Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

