

## Product data sheet

### Characteristics

# LVS04040

Distribution block, Linergy DX, 4P, 63A, 4 modules, 24 holes, quick connection top



### Main

Range	Linergy
Product or component type	Distribution block
Product name	Linergy DX
Range compatibility	Prisma PrismaSeT Pragma
Product compatibility	Spacial enclosures
IP degree of protection	IPxx B

### Complementary

Location of connection	Top
Mounting support	DIN rail
Poles description	4P
[Ue] rated operational voltage	440 V AC
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	6 kV
[Ie] rated operational current	63 A at 40 °C
[In] rated current	63 A at 40 °C
Connections - terminals	Supply: tunnel type terminal 16 mm <sup>2</sup> (flexible) Supply: tunnel type terminal 25 mm <sup>2</sup> (rigid) Distribution: spring terminal (phase), 12 x 2.5...6 mm <sup>2</sup> (flexible) Distribution: spring terminal (phase), 12 x 2.5...6 mm <sup>2</sup> (rigid) Distribution: spring terminal (neutral), 12 x 2.5...6 mm <sup>2</sup> (flexible) Distribution: spring terminal (neutral), 12 x 2.5...6 mm <sup>2</sup> (rigid)
9 mm pitches	8
Total number of 18 mm modules	4
Net weight	0.29 kg

### Environment

Pollution degree	3
Resistance to incandescent wire	960 °C conforming to IEC 60695-2-11
Standards	IEC 60947-7-1 IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	328.0 g
Package 1 Height	7.5 cm
Package 1 width	7.5 cm
Package 1 Length	10.5 cm
Unit Type of Package 2	S03

Number of Units in Package 2	30
Package 2 Weight	10.148 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm