

Product data sheet

Characteristics

TPCDIO05

function module, TransferPacT, Load shedding and Availability warning, output signal



Main

| | |
|---------------------------|--------------|
| Range of product | TransferPacT |
| Product or component type | I/O module |
| Device application | Signalling |

Complementary

| | |
|------------------------------------|---|
| Auxiliary contact composition | 2 NO + 1 NC |
| Signalling function | Load-shedding indication Output status |
| Auxiliary connection terminal | Screw clamp terminal 0.05...2.6 mm ² |
| Mounting mode | Plug-in |
| Mounting position | Left-bottom |
| [Ui] rated insulation voltage | 300 V AC |
| Tightening torque | 0.6 N.m +/- 0.1 N.m |
| Height | 56.5 mm |
| Width | 20 mm |
| Depth | 69 mm |
| Net weight | 40 g |
| Accessory / separate part category | Signalling accessory |







Environment

| | |
|-------------------------|------|
| IP degree of protection | IP20 |
| Pollution degree | 3 |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 4.5 cm |
| Package 1 Width | 10.5 cm |
| Package 1 Length | 11 cm |
| Package 1 Weight | 110 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 20 |
| Package 2 Height | 15 cm |
| Package 2 Width | 30 cm |
| Package 2 Length | 40 cm |
| Package 2 Weight | 2.38 kg |
| Package 3 Height | 15 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile |  End Of Life Information |