

SITEMATE ADAPTOR LEAD

3 way 16A adaptor lead single phase IEC

APPLICATIONS:

For use with temporary site lighting

CONSTRUCTION:

- **Cable:** 2 core 2.5mm² + 2.5mm² Screened Earth (CBS) Flexible cable 250/440V 90°C
- **Connector:** Scame 3 way 16A, 1ph, 2 pin + E - CEEFORM
- **Plug:** Scame 16A, 1ph, 2 pin + E - CEEFORM
- **Protection:** 15 Amp resettable overload

PRODUCT FEATURES:

- IP67 Plug IEC60309
- IP66 Connector IEC60309
- Earth Screened Flexible Cable (CBS)
- User resettable overload protection for added safety/compliance
- Available in 1 metre or 4 metre length

CHARACTERISTICS:

- Relevant standards: AS/NZS 3760, AS/NZS 5000.1



Code	Cable length	Supply Power	Socket Outlet
SMLA1M	1 metre	16A 1ph + N + E 230VAC IEC	3 x 16A 1ph + N + E 230VAC IEC
SMLA4M	4 metre	16A 1ph + N + E 230VAC IEC	3 x 16A 1ph + N + E 230VAC IEC

Sitemate Power Systems has taken every precaution to ensure accurate information on this data page, but accept no liability for any errors or omissions. Sitemate Power Systems reserves the right to modify specifications at any time.