



HO PLUS SERIES

Ultra Performance Flexible Rubber Cable



APPLICATIONS:

Hazardous Areas With correct explosion proof glands this cable can be installed in locations subject to explosion hazards rated 0.6/1kV (DIN VDE 0165).

Waste Water Treatment Plants Suitable for submersion in polluted liquids and aggressive environments up to 10 metres.

Lighting & Entertainment With its extra durable CPE sheath this cable is suitable for outdoor temporary power supplies and lighting leads.

Marine Flexible tinned copper cable for installation in pleasure craft and other marine applications.

Power Used on construction sites due to its outstanding flexibility, durability and industrial performance.

Pumping Suitable for permanent submersion to 200 metres.

Materials and Handling Systems Suitable for cable spring reeler and large energy chains.

PRODUCT FEATURES:

- ▶ Tinned fine stranded copper conductor
- ▶ UV stabilised
- ▶ Flame retardant
- ▶ Water and moisture resistant
- ▶ Good elongation at break
- ▶ Resistant to environmental factors such as oxidation, ozone and sunlight
- ▶ Suitable for permanent submersion to 200 metres
- ▶ Good tensile strength, tearing strength and abrasion resistance
- ▶ Heat, oil and chemical resistant (See Technical Section)

CONSTRUCTION:

Conductor Annealed tinned copper stranded high flexibility (Class 5).

Insulation EPR R90.

Sheath CPE Elastomer Rubber.

CHARACTERISTICS:

Operating Temperature Range Fixed -40°C to 90°C / Flexing -25°C to 90°C.

Maximum Conductor Temperature 90°C (Current ratings are based on 30°C air temp. See technical section for de-rating factors).

Rated Voltage H05=300/500V, H07=0.6/1kV.

Max AC Operating Voltage U_0 0.7kV.

Minimum Bending Radius Fixed 4 x cable diameter / flexing 6 x cable diameter / Drag chains and spring reeler 10 x cable diameter.

Sheath Colour Black.

Standard Core Colours

2 Core – Blue, Brown.

3 Core – Blue, Brown, Green/Yellow.

4 Core – Brown, Black, Grey, Green/Yellow.

Multi Core – Black Numbered + Green/Yellow.

Relevant Standards H07RN-F Type, DIN VDE 0295, DIN VDE 0165, IEC 60332-1, EN 50363, EN 50525-2-21, **RoHS** Compliant.

Code	No. of Cores x Size (mm ²)	Approx. Stranding No. of wires x mm	Approx. Overall Diameter +/- 15% (mm)	Approx. Weight (Kg/Km)	Nominal Amps un-enclosed protected from sun at 30°C fixed application Touching	3 Phase Volt Drop @ 50Hz / MAX. Conductor Temp: 90°C (Mv/A.m)
H05RN-F 300/500V						
H02/0.75B	2 x 0.75	24/0.20	6.6	62	12	54.800
H02/1.0B	2 x 1.0	32/0.20	7.0	72	20	46.800
H03G0.75B	3 x 0.75	24/0.20	7.2	77	12	54.800
H03G1.0B	3 x 1.0	32/0.20	7.5	125	20	46.800
H04G0.75B	4 x 0.75	24/0.20	7.8	78	11	54.800
H04G1.0B	4 x 1.0	32/0.20	8.2	155	17	46.800
H07RN-F 0.6/1kV						
H07G4.0B	7 x 4.0	56/0.30	22.8	660	27	10.200
H07G6.0B	7 x 6.0	84/0.30	23.3	956	35	6.800

Firstflex has taken every precaution to ensure accurate information in this catalogue, but accepts no liability for any errors or omissions. Firstflex reserves the right to modify specifications at any time.