Interlocked Switch Socket Outlets

Scame offers products suitable for installation into environments under potential risk of explosion. The Advance GRP series are made from glass reinforced polyester which guarantees excellent heat and fire resistance; it does not propagate flames, emit halogens or smoke.

IP67 - Advance Series

Code	Rating	Pins	Earth Position
415v RED			
568.3287	32 Amp	3 P + N + E	6H + MCB/RCD Mount
568.6386	63 Amp	3 P + E	6H + MCB/RCD Mount
568.6387	63 Amp	3 P + N + E	6H + MCB/RCD Mount

568 Series

125A Switched Interlocked Socket Outlet

The glass reinforced polyester combined with the thickness of the casing walls guarantee excellent mechanical resistance to impacts (IK10). Offering resistance to chemical agents and atmospheric agents making it suitable for most extreme environmental conditions. The double degree of protection IP66 guarantees seal against entry of solid objects or liquid, also outstanding resistance to UV radiation.

Technical Specifications	
Rated Current	125A
IP Rating	IP66
IK Rating	IK10
Rated Voltage	100÷690V
Operating Temperature	-25°C ~ 60°C
Self-extinguishing UL94	V0
Colour	RAL 7037 grey

503 Series

IP66 - Advance (GRP) Series

415v RED				
503.12586	125 Amp	3 P + E	6H	
503.12587	125 Amp	3 P + N + E	6H	

International Industrial Standard IEC60309-CEE17

Firstflex has taken every precaution to ensure accurate information in this catalogue, but accept no liability for any errors or omissions. Firstflex reserves the right to modify specifications at any time.