

Switches & Accessories



Rectangular Bulkhead Light - IP55

- For incandescent lamps
- Mizar series
- Max 60W
- Lampholder E27 (screw bulb)

Code: 786.2761 Indent Stock Item



Technical Specifications

IP Rating	IP55
Operating Temperature	Polycarbonate diffuser: -15°C~35°C
Glow Wire Test	650°C
Material	Engineering Plastic
IK Rating	IK04~IK07
Double Insulation	Yes
Colour of Diffuser	Red

Data Communications Enclosure

- IP66 rated enclosure even with cables connected.
- Tinted polycarbonate cover to see inside.
- Polycarbonate enclosure - shockproof, chemical and UV resistant.
- Accepts PDL 600 series mechanisms including: RJ45, CAT5, CAT6 (with/without POE) F-type TV, RCA, HDMI, BT Telephone.
- Ideal for external connections - phone, data cable, speakers, industrial access points and wash down areas.
- Flush wall mounting kit available (Code: 137.121)

Code: 137.COMM



Technical Specifications

	EN60670-1
IP Rating	IP66
Operating Temperature	-5°C to 60°C
Material	Polycarbonate
IK Rating	IK07
Cable Inserts	M20
Colour	BASE: RAL 7035 grey/ LID: smoke tinted transparent



Blank Plate for
Panel Cutouts
Code: 654.0100



Blank Plate for
4 Din Modules
Code: 654.0400



Blank Plate for
Panel Cutouts
► IP55
Code: 654.0120



4 DIN Terminal
Code: 654.0365



8 DIN Terminal
Code: 654.0363



12 DIN Terminal
Code: 654.0361

Domestic Outlets

Watertight Cover

- 10A or 15A single outlet - IP55



Code	Rating	Pins
570.5052A-10	10 Amp	2P+E
570.5052A-15	15 Amp	2P+E