

SIHF MULTI CORE SERIES

High Performance Flexible Silicone Rubber High Temperature Cable
300/500V 180°C



APPLICATIONS:

High Temperature Suitable for wiring on kilns, boilers, lighting and other high temperature applications and surfaces not exceeding 180°C.

Low Temperature Used for wiring in industrial cool stores and freezers to -60°C.

PRODUCT FEATURES:

- ▶ Halogen – Free IEC 60754
- ▶ Tinned fine stranded copper conductor
- ▶ High ignition or flashpoint
- ▶ Minimal change to dielectric strength at high temperature
- ▶ Minimal change to insulation resistance at high temperature
- ▶ In the event of a fire the silicone forms an insulating layer of SiO₂
- ▶ UV stabilised
- ▶ Flame retardant
- ▶ Resistant to environmental factors such as oxidation, ozone and sunlight
- ▶ Very good behaviour to variations of outdoor temperature
- ▶ Heat, oil and chemical resistant (See Technical Section)

CONSTRUCTION:

Conductor Annealed tinned copper stranded high flexibility (Class 5).

Insulation Silicone rubber.

Sheath Silicone rubber.

CHARACTERISTICS:

Operating Temperature Range Fixed -60°C to 180°C / Flexing -40°C to 180°C.

Maximum Conductor Temperature 180°C.

Rated Voltage Uo/U 300/500v.

Max AC Operating Voltage Uo 318v.

Minimum Bending Radius Fixed 4 x cable diameter /

Flexing 7.5 x cable diameter.

Sheath Colour Reddish-Brown.

Standard Core Colours

3 Core – Blue, Brown, Green/Yellow.

4 Core – Brown, Black, Grey, Green/Yellow.

5 Core – Blue, Brown, Black, Grey, Green/Yellow.

Multi Core – Black Numbered, Green/Yellow.

Relevant Standards IEC 60332-1, IEC 60754-2, IEC6 0228,

VDE 0472, VDE 0282, CE Directive 2006/95/EC,

RoHS Compliant.

Code	No. of Cores x Size (mm ²)	Approx. Stranding No. of wires x mm	Approx. Overall Diameter (mm)	Approx. Weight (Kg/Km)	Nominal Amps un-enclosed protected from sun @ 150°C fixed installation Touching or in ventilated ducts
SIHF3/0.75	3 x 0.75	24/0.20	6.8	76	12
SIHF3/1.0	3 x 1.0	32/0.20	7.4	93	15
SIHF3/1.5	3 x 1.5	30/0.25	8.0	117	18
SIHF3/2.5	3 x 2.5	50/0.25	9.7	179	26
SIHF4/0.75	4 x 0.75	24/0.20	7.8	101	12
SIHF4/1.5	4 x 1.5	30/0.25	8.8	145	18
SIHF4/2.5	4 x 2.5	50/0.25	10.6	222	26
SIHF4/4.0	4 x 4.0	56/0.30	13.2	346	34
SIHF4/6.0	4 x 6.0	84/0.30	15.6	497	44
SIHF4/10	4 x 10.0	80/0.40	19.1	778	61
SIHF5/0.5	5 x 0.5	16/0.20	7.8	59	3
SIHF5/1.5	5 x 1.5	30/0.25	9.6	175	18
SIHF5/2.5	5 x 2.5	50/0.25	11.6	268	26

Continued over page ▶

Firstflex has taken every precaution to ensure accurate information in this catalogue, but accepts no liability for omissions or errors. Firstflex reserves the right to modify specifications at any time.