

TC LOOP SERIES

High Performance Fixed
Instrumentation Traffic Loop Cable
250V 80°C



APPLICATIONS:

Traffic Signals Operating in the frequency range 20kHz to 200kHz.
Suitable for slots cut into the road surface.

PRODUCT FEATURES:

- ▶ UV resistant
- ▶ Flame retardant
- ▶ Heat, oil and chemical resistant (See Technical Section)

CONSTRUCTION:

Conductor Annealed plain copper stranded (Class 2).
Insulation PP - Polypropylene.

CHARACTERISTICS:

Operating Temperature Range Fixed -10°C to 80°C.

Maximum Conductor Temperature 80°C.

Min. Insulation Resistance 20G Ω /km @ 500Vdc.

Rated Voltage 250V.

Minimum Bending Radius 12 x cable diameter.

Sheath Colour Black.

Relevant Standards AS/NZS 2276.3, AS/NZS 1125, AS/NZS 1660,
AS/NZS 1049 and **RoHS** Compliant.

Code	No. of Cores x Size (mm ²)	Approx. Stranding No. of wires x size	Insulation Thickness (mm)	Max D.C. Resistance of conductor at 20°C Ω /km	Frequency Range (kHz)	Approx. Overall Diameter (mm)
TC001.5BK	1 x 1.5	7/0.5	0.8	13.8	20 to 200	3.5