

Spec Sheet: RS Fuse Fitting 20A

- Insulating sleeves to protect cable entry.
- Full shrouded contacts, IP20 degree of protection.
- Made from tough flame retardant non-hydroscopic material.
- Anti-vibration contact design.
- Optional DIN rail mounting bracket.

Standard

Australian Standard AS60269



Range

Rated current (Ie)	20A
Rated voltage (Ue)	690V
Rated peak withstand current	80kA
Rated impulse withstand voltage (Uimp)	8kV
Screw mounting size (all)	M5
Weight 1P (Front wire)	0.1kg
Max Cable Size (front / rear)	10mm ²
Maximum tightening torque (front)	1.5-2Nm
Fuse type (suit all)	NIT ₋

Rated Current (A)	Type of Connection	Colour	Pack Quantity	Catalogue Number
20A	Front Wire	Black	10	RS20H
	Busbar / Front wire	Black		RS20P
	2 Stud rear	Black		RS20PH
	Back Wire	Black		RS20BW
	Front Wire	White		RS20HWH
	2 Stud rear	White		RS20PWH
	Solid Neutral Link	-		RS20CLINK
	Protective Boot – suit rear stud	Black	10	RS20/32S
	Padlock barrier	Yellow	3	RS20LOCK
	DIN rail mounting clip	-	1	RS20A
	Red safety handle	Red	1	RS20RED

Dimensions

