

Spec Sheet: RS Fuse Fitting 32A

- Insulating sleeves to protect cable entry.
- Full shrouded contacts, IP20 degree of protection.
- Made from tough flame retardant non-hydroscopic material.
- Anti-vibration contact design.
- Tapered shank on fuse fixing screws, easy re-entry.

Standards

Australian Standard AS60269



Range

Rated current (Ie)	32A
Rated voltage (Ue)	690V
Rated peak withstand current	80kA
Rated impulse withstand voltage (Uimp)	8kV
Screw mounting size (all)	M5
Weight 1P (Front wire)	0.24kg
Max Cable Size (front)	25mm ²
Max Cable Size (rear)	16mm ²
Maximum tightening torque (front)	1.5-2Nm
Fuse type (suit all)	TIA ₁

Rated Current (A)	Type of Connection	Colour	Pack Quantity	Catalogue Number
32A	Front Wire	Black	10	RS32H
	Busbar / Front wire	Black		RS32P
	2 Stud rear	Black		RS32PH
	Back Wire	Black		RS32BW
	Front Wire	White		RS32HWH
	2 Stud rear	White		RS32PWH
	Solid Neutral Link	-	10	RS32CLINK
	Protective Boot – suit rear stud	Black		RS20/32S
	Padlock barrier	Yellow		RS32LOCK
	DIN rail mounting clip	-		RS32A
	Red safety handle	Red		RS32RED

Dimensions

