

Spec Sheet: RS Fuse Fitting 32A

- Insulating sleeves to protect cable entry.
- Full shrouded contacts, IP20 degree of protection.
- Made from tough flame retardant non-hygroscopic material.
- Anti-vibration contact design.
- Tapered shank on fuse fixing screws, easy re-entry.

Standards

Australian Standard AS60269



Range

Rated current (Ie)	63A
Rated voltage (Ue)	690V
Rated peak withstand current	80kA
Rated impulse withstand voltage (Uimp)	8kV
Screw mounting size (all)	M5
Weight 1P (Front wire)	0.32kg
Max Cable Size (front)	50mm ²
Max Cable Size (rear)	35mm ²
Maximum tightening torque (front)	2.5-3Nm
Fuse type (suit all)	TIA/TIS

Rated Current (A)	Type of Connection	Colour	Pack Quantity	Catalogue Number
63A	Front Wire	Black	10	RS63H
	Busbar / Front wire	Black		RS63PH
	2 Stud rear	Black		RS63P
	Back Wire	Black		RS63BW
	Front Wire	White		RS63HWH
	2 Stud rear	White		RS63PWH
	Solid Neutral Link	-	1	RS63CLINK
	Padlock barrier	Yellow	1	RS63LOCK
	Red safety handle	Red	1	RS63RED

Dimensions

