Medium wall 3/1 black heat-shrink tubing with adhesive 85/25 mm 4FT

Aucun visuel

Caracteristics

Référence Nouvelle-Zélande : *BIZ218026*
Wall Ø before shrinking *(mm)* : *85*
Wall Ø after shrinking *(mm)* : *25*

GENERAL INFORMATION

Description
Medium wall 3/1 heat-shrink tubing with adhesive.

Technical details
Medium wall, 3/1 shrinkage in length 1.2 meter.
Heat-shrink tubing in polyolefin with hot melt adhesive.
Flame retardant: outer jacket layer.
Working temperature: -45 °C to +125 °C.
Shrink temperature: 125 °C.
Dielectric strength (IEC 243): 20 kV/mm.
Tensile strength: 10.4 Mpa.
Rate voltage: 600 V.
Self-extinguishing in accordance with UL224.
Color: black.

Application(s)
For general and specific applications in the following areas: electrical insulation, marking and identification, protection (mechanical against corrosion), management and maintenance of wires.

LOGISTIC INFORMATION

Packaging

No packaging
Height (cm) : 4.25
Length (cm) : 120
Depth (cm) : 12.8
Net weight (kg) : 0.576
Gross weight (kg) : 0.66

3 700882 101112

Outer package 1

x 1

Bag
Height (cm) : 25
Length (cm) : 120
Depth (cm) : 12.8
Net weight (kg) : 5.8
Gross weight (kg) : 6.6

3 700882 125835

Outer package 2

x 25

Carton box
Height (cm) : 25
Length (cm) : 130
Depth (cm) : 45
Net weight (kg) : 14.4
Gross weight (kg) : 16.5

3 700882 126573

Outer package 3

x 300

Pallet
Height (cm) : 125
Length (cm) : 130
Depth (cm) : 90
Net weight (kg) : 172.8
Gross weight (kg) : 41.3

3 700882 127310