

Thin wall 2/1 blue heat-shrink tubing without adhesive 20/10 mm 4FT

Aucun visuel

Caracteristics

Référence Nouvelle-Zélande : [BIZ218057](#)Color : [Blue](#)Wall Ø before shrinking (mm) : [20](#)Wall Ø after shrinking (mm) : [10](#)

GENERAL INFORMATION

Description

Thin wall 2/1 heat-shrink tubing without adhesive.

Technical details

Thin wall, 2/1 shrinkage in length 1.2 meter.

Heat-shrink tubing in flexible flame retardant polyolefin (except clear).

Working temperature: -45 °C to +125 °C (clear is -45 °C to +105 °C).

Shrink temperature: 120 °C (clear is 105 °C).

Dielectric strength (IEC 243): 15 kV/mm.

Tensile strength: 10.4 Mpa.

Rate voltage: 600 V.

Self-extinguishing in accordance with UL224 (except clear).

Application(s)

For general and specific applications in the following areas: electrical insulation, marking and identification, protection (mechanical against corrosion), management and maintenance of wires.

ADDITIONAL INFORMATION

Color and diameter next pages.

LOGISTIC INFORMATION

Packaging



No packaging

Height (cm) : 1

Length (cm) : 120

Depth (cm) : 3

Net weight (kg) : 0.043

Gross weight (kg) : 0.046



3 700882 101297

Outer package 1



x 10

Bag

Height (cm) : 15

Length (cm) : 120

Depth (cm) : 3

Net weight (kg) : 0.43

Gross weight (kg) : 0.46



3 700882 126016

Outer package 2



x 200

Carton box

Height (cm) : 16

Length (cm) : 130

Depth (cm) : 20

Net weight (kg) : 10.1

Gross weight (kg) : 10.7



3 700882 126757

Outer package 3



x 5600

Pallet

Height (cm) : 115

Length (cm) : 130

Depth (cm) : 80

Net weight (kg) : 282.8

Gross weight (kg) : 299.6



3 700882 127495