

Thin wall 2/1 red heat-shrink tubing without adhesive 2/1 mm 4FT

Aucun visuel

Caracteristics

Référence Nouvelle-Zélande : [BIZ218072](#)Color : [Red](#)Wall Ø before shrinking (mm) : [2](#)Wall Ø after shrinking (mm) : [1](#)

GENERAL INFORMATION

Description

Thin wall 2/1 heat-shrink tubing without adhesive.

Technical details

Thin wall, 2/1 shrinkage in length 1.2 meter.

Heat-shrink tubing in flexible flame retardant polyolefin (except clear).

Working temperature: -45 °C to +125 °C (clear is -45 °C to +105 °C).

Shrink temperature: 120 °C (clear is 105 °C).

Dielectric strength (IEC 243): 15 kV/mm.

Tensile strength: 10.4 Mpa.

Rate voltage: 600 V.

Self-extinguishing in accordance with UL224 (except clear).

Application(s)

For general and specific applications in the following areas: electrical insulation, marking and identification, protection (mechanical against corrosion), management and maintenance of wires.

ADDITIONAL INFORMATION

Color and diameter next pages.

LOGISTIC INFORMATION

Packaging



No packaging

Height (cm) : 0.2

Length (cm) : 120

Depth (cm) : 0.2

Net weight (kg) : 0.002

Gross weight (kg) : 0.002



3 700882 101446

Outer package 1



x 10

Bag

Height (cm) : 1.5

Length (cm) : 120

Depth (cm) : 0.3

Net weight (kg) : 0.02

Gross weight (kg) : 0.02



3 700882 126160

Outer package 2



x 750

Carton box

Height (cm) : 8

Length (cm) : 130

Depth (cm) : 20

Net weight (kg) : 3

Gross weight (kg) : 3



3 700882 126900

Outer package 3



x 42000

Pallet

Height (cm) : 115

Length (cm) : 130

Depth (cm) : 80

Net weight (kg) : 168

Gross weight (kg) : 168



3 700882 127648