Thin wall 2/1 white heat-shrink tubing without adhesive 1.5/0.8 mm 1.2 m

Aucun visuel

Caracteristics

Référence Nouvelle-Zélande : ***BIZ218128***
Color : ***White***
Wall Ø before shrinking *(mm)* **:** ***1.5***
Wall Ø after shrinking *(mm)* **:** ***0.8***

GENERAL INFORMATION

Description
Thin wall 2/1 heat-shrink tubing without adhesive.

Technical details
Thin wall, 2/1 shrinkage in length 1.2 meter.
Heat-shrink tubing in flexible flame retardant polyolefin (except clear).
Working temperature: -45 °C to +125 °C (clear is -45 °C to +105 °C).
Shrink temperature:120 °C (clear is 105 °C).
Dielectric strength (IEC 243): 15 kV/mm.
Tensile strength: 10.4 Mpa.
Rate voltage: 600 V.
Self-extinguishing in accordance with UL224 (except clear).

Application(s)
For general and specific applications in the following areas: electrical insulation, marking and identification, protection (mechanical against corrosion), management and maintenance of wires.

ADDITIONAL INFORMATION

Color and diameter next pages.

LOGISTIC INFORMATION

Packaging



No packaging
Height (cm) : 0.15
Length (cm) : 120
Depth (cm) : 0.15
Net weight (kg) : 0.002
Gross weight (kg) : 0.002

3 700882 125712

Outer package 1



x 10

Bag
Height (cm) : 1.5
Length (cm) : 120
Depth (cm) : 0.3
Net weight (kg) : 0.02
Gross weight (kg) : 0.02

3 700882 129550

Outer package 2



x 1000

Carton box
Height (cm) : 8
Length (cm) : 130
Depth (cm) : 20
Net weight (kg) : 3
Gross weight (kg) : 3

3 700882 129796

Outer package 3



x 56000

Pallet
Height (cm) : 115
Length (cm) : 130
Depth (cm) : 80
Net weight (kg) : 168
Gross weight (kg) : 168

3 700882 130037