

Black high performance vinyl tape 19 mm x 20 m x 0.18 mm



Characteristics

Color : **Black**

Length (m) : **20**

Width (mm) : **19**

Thickness (mm) : **0.18**

Benefits

- High resistance to extreme temperatures.
- UV resistant.
- No feathering.

Compliance marks



GENERAL INFORMATION

Description

High performance electrical vinyl tape.
Synthetic rubber adhesive mass.
Flexible, press-on adhesive tape.
High resistance to sunshine, water, oil, acid, alkali and corrosive chemicals.
Flame-retardant/Self-extinguishing.
Lead free.

Technical details

Dimensions: 19 mm x 20 m x 0.18 mm.
Tensile strength: 32 N/cm.
Elongation at break: 240 %.
Adhesion to steel 2B: 2.25 N/cm.
Adhesion to backing: 2.15 N/cm.
Dielectric strength: 40 kV/mm.
Insulation resistance: $5.0 \times 10^9 \Omega/25 \text{ mm}$.
Operating temperature: -18 °C to +105 °C.
Application temperature: -10 °C to +40 °C.
Color: black.

Advice

For making cable harnesses, apply the product with at least a 50 % covering.

Application(s)

Implementation of cable harnesses, splicing, wire and cable terminations.
Repairing conduits.
Electrical insulation at high and low temperatures.
Suitable for outdoor use, UV-resistant.



LOGISTIC INFORMATION

 Packaging**Plastic case**

Height (cm) : 2.3

Length (cm) : 9.6

Depth (cm) : 9.6

 Net weight (kg) : 0.09 Gross weight (kg) : 0.11 Outer package 1

x 100

Carton box

Height (cm) : 25

Length (cm) : 52

Depth (cm) : 22

 Net weight (kg) : 11 Gross weight (kg) : 11.2 Outer package 2

x 2000

Pallet

Height (cm) : 115

Length (cm) : 125

Depth (cm) : 80

 Net weight (kg) : 224 Gross weight (kg) : 244