Stainless steel barb locking PA 6.6 cable tie 102 x 2.4 mm transparent (x 100)



Caracteristics

Color : ***Transparent***
Length *(mm)* **:** ***102***
Width *(mm)* **:** ***2.4***
Thickness *(mm)* **:** ***1.0***
Maximum clamping Ø *(mm)* **:** ***23***
Traction strength *(N)* **:** ***80***
Quantity per box : ***100***

Benefits

- No resistance on tightening.
- High level of abrasion resistance.
- Halogen-free.
- UV-resistant.

Compliance marks

GENERAL INFORMATION

Technical details
Pull-tie material: polyamide 6.6.
Raw material flammability: UL94V-2.
Barb material: stainless steel 304.
Installation temperature: - 40 to +60 °C.
Operating temperature: -40 to +85 °C.

Application(s)
These cable ties are designed for interior and exterior fixing applications. Perfect for environments where vibration is present, the metal barb ensures regular high performance levels and long-term reliability.

LOGISTIC INFORMATION

Packaging

Basic plastic bag
Height (cm) : 1
Length (cm) : 20
Depth (cm) : 11
Net weight (kg) : 0.026
Gross weight (kg) : 0.028

3 700882 154705

Outer package 1

x 300

Carton box
Height (cm) : 46
Length (cm) : 36
Depth (cm) : 27
Net weight (kg) : 8.5
Gross weight (kg) : 9.5

3 700882 155627

Outer package 2

x 6000

Pallet
Height (cm) : 118
Length (cm) : 120
Depth (cm) : 80
Net weight (kg) : 190
Gross weight (kg) : 210

3 700882 155863