

Stainless steel barb locking PA 6.6 cable tie 284 x 3.6 mm transparent (x 100)



Characteristics

Color : **Transparent**
 Length (mm) : **284**
 Width (mm) : **3.6**
 Thickness (mm) : **1.2**
 Maximum clamping Ø (mm) : **80**
 Traction strength (N) : **178**
 Quantity per box : **100**

Benefits

- No resistance on tightening.
- High level of abrasion resistance.
- Halogen-free.
- UV-resistant.

Compliance marks



GENERAL INFORMATION

■ Technical details

Pull-tie material: polyamide 6.6.
 Raw material flammability: UL94V-2.
 Barb material: stainless steel 304.
 Installation temperature: - 40 to +60 °C.
 Operating temperature: -40 to +85 °C.

■ Application(s)

These cable ties are designed for interior and exterior fixing applications. Perfect for environments where vibration is present, the metal barb ensures regular high performance levels and long-term reliability.

LOGISTIC INFORMATION

■ Packaging



Basic plastic bag

Height (cm) : 1
 Length (cm) : 39
 Depth (cm) : 11
 Net weight (kg) : 0.132
 Gross weight (kg) : 0.134



■ Outer package 1



x 100

Carton box

Height (cm) : 46
 Length (cm) : 36
 Depth (cm) : 27
 Net weight (kg) : 13.4
 Gross weight (kg) : 14.4



■ Outer package 2



x 2000

Pallet

Height (cm) : 118
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 288
 Gross weight (kg) : 308

