

Stainless steel barb locking PA 6.6 cable tie 350 x 8 mm transparent (x 50)



Characteristics

Color : **Transparent**Length (mm) : **350**Width (mm) : **8**Thickness (mm) : **1.6**Maximum clamping Ø (mm) : **92**Traction strength (N) : **500**Quantity per box : **50**

Benefits

- No resistance on tightening.
- High level of abrasion resistance.
- Halogen-free.
- UV-resistant.

Compliance marks



GENERAL INFORMATION

■ Technical details

Pull-tie material: polyamide 6.6.

Raw material flammability: UL94V-2.

Barb material: stainless steel 304.

Installation temperature: - 40 to +60 °C.

Operating temperature: -40 to +85 °C.

■ Application(s)

These cable ties are designed for interior and exterior fixing applications. Perfect for environments where vibration is present, the metal barb ensures regular high performance levels and long-term reliability.

LOGISTIC INFORMATION

■ Packaging



Basic plastic bag

Height (cm) : 1

Length (cm) : 46

Depth (cm) : 13

Net weight (kg) : 0.208

Gross weight (kg) : 0.21



3 700882 154767

■ Outer package 1



x 50

Carton box

Height (cm) : 46

Length (cm) : 36

Depth (cm) : 27

Net weight (kg) : 10.5

Gross weight (kg) : 11.5



3 700882 155689

■ Outer package 2



x 1000

Pallet

Height (cm) : 118

Length (cm) : 120

Depth (cm) : 80

Net weight (kg) : 230

Gross weight (kg) : 250



3 700882 155924