

Stainless steel barb locking PA 6.6 cable tie 102 x 2.4 mm UV black (x 1000)



Characteristics

Color : **Black**
 Length (mm) : **102**
 Width (mm) : **2.4**
 Thickness (mm) : **1.0**
 Maximum clamping Ø (mm) : **23**
 Traction strength (N) : **80**
 Quantity per box : **1000**

Benefits

- No resistance on tightening.
- High level of abrasion resistance.
- Halogen-free.
- UV-resistant.

Compliance marks



GENERAL INFORMATION

Technical details

Pull-tie material: polyamide 6.6.
 Raw material flammability: UL94V-2.
 Barb material: stainless steel 304.
 Installation temperature: - 40 to +60 °C.
 Operating temperature: -40 to +85 °C.

Application(s)

These cable ties are designed for interior and exterior fixing applications. Perfect for environments where vibration is present, the metal barb ensures regular high performance levels and long-term reliability.

LOGISTIC INFORMATION

Packaging



Basic plastic bag

Height (cm) : 1
 Length (cm) : 28
 Depth (cm) : 23
 Net weight (kg) : 0.31
 Gross weight (kg) : 0.312



Outer package 1



x 25

Carton box

Height (cm) : 46
 Length (cm) : 36
 Depth (cm) : 27
 Net weight (kg) : 7.8
 Gross weight (kg) : 8.800000



Outer package 2



x 500

Pallet

Height (cm) : 118
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 176
 Gross weight (kg) : 196

