

Underground marking tape warning electrical cable below orange NZ 300 m



Caracteristics

Color : **Orange**

Référence Nouvelle-Zélande : **BIZUGT300**

Length (m) : **300**

Width (mm) : **98**

Thickness (mm) : **0.08**

Material : **Polyethylene**



GENERAL INFORMATION

Description

Non detectable underground tape.

Technical details

Core inside Ø: 76 mm.

Load at yield

Mounting direction: 71.2 N.

Transverse direction: 60.0 N.

Load at break

Mounting direction: 109.0 N.

PSI: 18.6 MPa.

Transverse direction: 104.5 N.

PSI: 17.9 MPa.

Elongation at break

Mounting direction: 71.2 N.

Transverse direction: 60.0 N.

PPT resistance

Mounting direction: 60 N.

Transverse direction: 62.3 N.

Tongue tear

Mounting direction: 13.2 N.

Transverse direction: 22.7 N.

Application(s)

For protection, location and identification of underground utility installations.

LOGISTIC INFORMATION

Packaging



Color sticker

Height (cm) : 10.3
Length (cm) : 19.6
Depth (cm) : 19.6
Net weight (kg) : 2.3
Gross weight (kg) : 2.31



Outer package 1



x 8

Carton box

Height (cm) : 22
Length (cm) : 41
Depth (cm) : 41
Net weight (kg) : 18.48
Gross weight (kg) : 18.98



Outer package 2



x 272

Pallet

Height (cm) : 123
Length (cm) : 120
Depth (cm) : 100
Net weight (kg) : 645.320000
Gross weight (kg) : 655.320000

