

Biz'gel Express sealing gel, 280 ml cartridge

Mono-component ready-to-use injectable gel!

Aucun visuel

Caracteristics

Référence Nouvelle-Zélande : **BIZ710000**

Net volume (ml) : **280**

Norms

> IP 68

Benefits

- Already cross-linked, ready to use.
- Reusable.
- Self-amalgamating.
- Usable immediately at low temperature down to -40 °C!
- No mixing, no waiting time.
- Easily re-accessible.
- Non toxic.
- No shelf-life.



GENERAL INFORMATION

Description

Injectable and ready-to-use mono-component gel in 280 ml cartridge.

Technical details

Dielectric strength: > 23 kV/mm.

Voltage: up to 1 kV.

Installation temperature: -40 °C to +110 °C.

Operating temperature after polymerization: -60 °C to +200 °C.

Advice

Use a cartridge gun.

Application(s)

Sealing and insulation of electrical connections.

Ideal for watertightness of confined junction boxes, just inject BIZ'GEL EXPRESS regardless of the position of your junction box or connection system.

Ideal solution for watertightness of all junction boxes in your worksites!



ACCESSORIES



**GUN FOR CARTRIDGES
AND INTUMESCENT
FOAM**



TECHNICAL DOCUMENT(S)

Technical documentation available on our website :



SDS



LOGISTIC INFORMATION

Packaging



Carton box

Height (cm) : 23.8

Length (cm) : 6.4

Depth (cm) : 6.4

Net weight (kg) : 0.375

Gross weight (kg) : 0.375



3 700420 319498

Outer package 1



x 24

Carton box

Height (cm) : 26

Length (cm) : 27

Depth (cm) : 40

Net weight (kg) : 9

Gross weight (kg) : 9.5



3 700420 319672

Outer package 2



x 576

Pallet

Height (cm) : 105

Length (cm) : 80

Depth (cm) : 120

Net weight (kg) : 228

Gross weight (kg) : 258



3 700420 319733