

Cable tie UNITY UV RESISTANT black 160 x 4.8 mm (x 100)



Characteristics

Length : **160**
 Width : **4.8**
 Thickness : **1.3**
 Maximum clamping Ø : **38**
 Traction strength : **222**
 Quantity per bag : **100**

Norms

> EN 62275

Benefits

- These cable ties last 3-4 times longer than standard cable ties exposed to UV light.

Compliance marks



GENERAL INFORMATION

Technical details

Polyamide 6.6 with additive guaranteeing resistance to UV rays.

Operating temperature (°C): -40 to +85.

Installation temperature (°C): > = 0.

Raw material flammability: UL94 V-2.

Colour: black.

Application(s)

For attaching outdoor cables exposed to UV light.

LOGISTIC INFORMATION

Packaging



Zippable plastic bag with tear-off

Height (cm) : 5

Length (cm) : 27

Depth (cm) : 13

Net weight (kg) : 0.12

Gross weight (kg) : 0.13



3 700882 198686

Outer package 1



x 100.00

Carton box

Height (cm) : 23

Length (cm) : 57

Depth (cm) : 38

Net weight (kg) : 11.88

Gross weight (kg) : 14.43



3 701395 100463

Outer package 2



x 1600.00

Pallet

Height (cm) : 107

Length (cm) : 120

Depth (cm) : 80

Net weight (kg) : 230.9

Gross weight (kg) : 246.9



3 701395 100791