Cable tie UNITY UV RESISTANT black 200 x 2.5 mm (x 100)

Caracteristics

Length : *200*
Width : *2.5*
Thickness : *1.2*
Maximum clamping Ø : *53*
Traction strength : *80*
Quantity per bag : *100*

Norms

> EN 62275

Benefits

- These cable ties last 3-4 times longer than standard cable ties exposed to UV light.

Compliance marks

CE

GENERAL INFORMATION

Technical details

Polyamide 6.6 with additive guaranteeing resistance to UV rays.
Operating temperature (°C): -40 to +85.
Installation temperature (°C): > = 0.
Raw material flammability: UL94 V-2.

Colour: black.

Application(s)

For attaching outdoor cables exposed to UV light.

LOGISTIC INFORMATION

Packaging

Zippable plastic bag with tear-off
Height (cm) : 2
Length (cm) : 32
Depth (cm) : 11
Net weight (kg) : 0.06
Gross weight (kg) : 0.06

3 700882 198693

Outer package 1

Carton box
Height (cm) : 31
Length (cm) : 57
Depth (cm) : 38
Net weight (kg) : 12.32
Gross weight (kg) : 15.56

x 220.00

3 701395 100470

Outer package 2

Pallet
Height (cm) : 108
Length (cm) : 120
Depth (cm) : 80
Net weight (kg) : 186.74
Gross weight (kg) : 202.74

x 2640.00

3 701395 100807