

Cable tie UNITY UV RESISTANT black 200 x 4.8 mm (x 100)



Characteristics

Length : **200**
Width : **4.8**
Thickness : **1.3**
Maximum clamping Ø : **50**
Traction strength : **222**
Quantity per bag : **100**

Norms

> EN 62275

Benefits

- These cable ties last 3-4 times longer than standard cable ties exposed to UV light.

Compliance marks



GENERAL INFORMATION

Technical details

Polyamide 6.6 with additive guaranteeing resistance to UV rays.
Operating temperature (°C): -40 to +85.
Installation temperature (°C): > = 0.
Raw material flammability: UL94 V-2.

Colour: black.

Application(s)

For attaching outdoor cables exposed to UV light.

LOGISTIC INFORMATION

Packaging



Zippable plastic bag with tear-off

Height (cm) : 5
Length (cm) : 32
Depth (cm) : 13
Net weight (kg) : 0.14
Gross weight (kg) : 0.15



3 700882 198723

Outer package 1



Carton box

Height (cm) : 20
Length (cm) : 57
Depth (cm) : 38
Net weight (kg) : 12.46
Gross weight (kg) : 14.5



3 701395 100500

Outer package 2



Pallet

Height (cm) : 95
Length (cm) : 120
Depth (cm) : 80
Net weight (kg) : 232.07
Gross weight (kg) : 248.07



3 701395 100838