Cable tie UNITY UV RESISTANT black 540 x 7.6 mm (x 50)

Caracteristics

Length : *540*
Width : *7.6*
Thickness : *1.6*
Maximum clamping Ø : *140*
Traction strength : *534*
Quantity per bag : *50*

Norms

> EN 62275

Benefits

- These cable ties last 3-4 times longer than standard cable ties exposed to UV light.

Compliance marks

CE

GENERAL INFORMATION

Technical details
Polyamide 6.6 with additive guaranteeing resistance to UV rays.
Operating temperature (°C): -40 to +85.
Installation temperature (°C): > = 0.
Raw material flammability: UL94 V-2.

Colour: black.

Application(s)
For attaching outdoor cables exposed to UV light.

LOGISTIC INFORMATION

Packaging

Polybag with colored label
Height (cm) : 4
Length (cm) : 68
Depth (cm) : 13
Net weight (kg) : 0.38
Gross weight (kg) : 0.39

3 700882 198914

Outer package 1

Carton box
Height (cm) : 27
Length (cm) : 57
Depth (cm) : 38
Net weight (kg) : 15.14
Gross weight (kg) : 17.86

x 40.00

3 701395 100692

Outer package 2

Pallet
Height (cm) : 123
Length (cm) : 120
Depth (cm) : 80
Net weight (kg) : 285.71
Gross weight (kg) : 301.71

x 640.00

3 701395 101026