Electrical insulation tape 20 m x 19 mm x 0.15 mm green (x 8)



Caracteristics

Colour : ***Green***
Length : ***20***
Width : ***19***
Thickness : ***0.15***
Quantity : ***8***

Norms

> EN 60454, classé IEC 60454-3-1-7/F-PVCP/90.

GENERAL INFORMATION

Description

Electrical insulation, protection and identification.
General use.
Plasticized PVC tapes, synthetic rubber adhesive mass.
Pressure-sensitive flexible tape.
Flame-retardant.
Acid and alkali resistant.
Lead free.

Technical details

Dimensions: 19 mm x 20 m x 0.15 mm.
Tensile strength: > 28 N/cm.
Elongation at break: > 200 %.
Adhesion to steel 2B: 2.2 N/cm.
Adhesion to backing: 2.0 N/cm.
Dielectric strength: 45 kV/mm.
Insulation resistance: 10^{11} Ω/25 mm.
Operating temperature: 0 °C to +90 °C.

Advice

When making cable looms, apply the product over a minimum of 50 % of the surface.

Instructions

1. Apply the product at a temperature between -10 °C and +40 °C.

LOGISTIC INFORMATION

Packaging



Plastic film
Height (cm) : 16
Length (cm) : 7.6
Depth (cm) : 7.6
Net weight (kg) : 0.66
Gross weight (kg) : 0.67

3 700420 318446

Outer package 1



x 15

Carton box
Height (cm) : 17.5
Length (cm) : 40
Depth (cm) : 24.5
Net weight (kg) : 9.85
Gross weight (kg) : 10.15

3 700420 326960

Outer package 2



x 675

Pallet
Height (cm) : 109
Length (cm) : 120
Depth (cm) : 80
Net weight (kg) : 444
Gross weight (kg) : 480

3 700420 390091