

Electrical insulation tape 20 m x 19 mm x 0.15 mm green/yellow (x 8)



Characteristics

Colour : **Yellow/green**

Length : **20**

Width : **19**

Thickness : **0.15**

Quantity : **8**

Norms

> EN 60454, classé IEC
60454-3-1-7/F-
PVCP/90.



GENERAL INFORMATION

Description

Electrical insulation, protection and identification.
General use.
Plasticized PVC tapes, synthetic rubber adhesive mass.
Pressure-sensitive flexible tape.
Flame-retardant.
Acid and alkali resistant.
Lead free.

Technical details

Dimensions: 19 mm x 20 m x 0.15 mm.
Tensile strength: > 28 N/cm.
Elongation at break: > 200 %.
Adhesion to steel 2B: 2.2 N/cm.
Adhesion to backing: 2.0 N/cm.
Dielectric strength: 45 kV/mm.
Insulation resistance: $10^{11} \Omega/25 \text{ mm}$.
Operating temperature: 0 °C to +90 °C.

Advice

When making cable looms, apply the product over a minimum of 50 % of the surface.

Instructions

1. Apply the product at a temperature between -10 °C and +40 °C.



LOGISTIC INFORMATION

 Packaging**Plastic film**

Height (cm) : 16

Length (cm) : 7.6

Depth (cm) : 7.6

 Net weight (kg) : 0.66 Gross weight (kg) : 0.67

3 700420 318477

 Outer package 1

x 15

Carton box

Height (cm) : 17.5

Length (cm) : 40

Depth (cm) : 24.5

 Net weight (kg) : 9.85 Gross weight (kg) : 10.15

3 700420 326991

 Outer package 2

x 675

Pallet

Height (cm) : 109

Length (cm) : 120

Depth (cm) : 80

 Net weight (kg) : 444 Gross weight (kg) : 480

3 700420 341918