

Double sided foam tape 24 mm x 10 m



Characteristics

NZ_PART # : BIZ390492

Colour : White

Length : 10

Width : 24

Thickness : 1

Benefits

- For interior and exterior use (good UV moisture and solvent resistance).
- Excellent shear strength.
- Can be torn by hand.



GENERAL INFORMATION

Description

Double-sided foam tape, solvent-based acrylic adhesive.

Technical details

Adhesion on steel: N/cm: 12.

Breaking load: N/mm²: 65/10.

Temperature resistance: -15 to +100 °C.

Application temperature: 0 to +35 °C.

Bonding period: 24 h at 23 °C.

Ideal storage temperature: +10 to +30 °C.

Application(s)

Assembly operations for which good load-bearing capacity is required.

Fitting mirrors, beading, and mouldings.

Signs and panels.



LOGISTIC INFORMATION

Packaging



Roll

Height (cm) : 2.4

Length (cm) : 14

Depth (cm) : 14

Net weight (kg) : 0.09

Gross weight (kg) : 0.09



3 700882 179395

Outer package 1



x 24

Carton box

Height (cm) : 16.8

Length (cm) : 30

Depth (cm) : 31

Net weight (kg) : 2.04

Gross weight (kg) : 2.54



3 700882 180643

Outer package 2



x 1344

Pallet

Height (cm) : 130

Length (cm) : 120

Depth (cm) : 80

Net weight (kg) : 114.24

Gross weight (kg) : 157.24



3 700882 180674