


Bi-metal CLIC II hole saw Ø 16 mm



Characteristics

Ø : 16

Depth of cut : 44

Steel : 580-300

Stainless steel : 300-175

Recommended speed in wood and PVC : 3000-2500

Materials

- ✓ Metal
- ✓ Wood
- ✓ Plasterboard

GENERAL INFORMATION

Description

Supplied without shaft or pilot drill.

Technical details

Material: HSS steel with 8% cobalt.

Teeth per inch: 4/6.

Advice

Do not use with hammer mode.

Application(s)

Ideally suited for steel, cast iron, aluminium (alloyed and non alloyed), non-ferrous metals, gypsum board, as well as natural and hard wood.

Instructions

1. To be fitted onto a hole saw shank CLIC II BIZ 780 150 or BIZ 780 151.

ADDITIONAL INFORMATION

Hardness: 65-67 HRC.

Diameter and speed of use on next page.

ACCESSORIES



HEX. SHAFT FOR CLIC II HOLE SAW WITH HSS PILOT DRILL 120 MM



HSS PILOT DRILL FOR CLIC II HOLE SAW 120 MM


LOGISTIC INFORMATION
Packaging

Blister package
Height (cm) : 16.6

Length (cm) : 5.2

Depth (cm) : 5.2

Net weight (kg) : 0.05

Gross weight (kg) : 0.07

3 700420 341628
Outer package 1


x 6

Carton box
Height (cm) : 18

Length (cm) : 20.7

Depth (cm) : 13.2

Net weight (kg) : 0.41

Gross weight (kg) : 0.49

3 700420 339847
Outer package 2


x 72

Carton box
Height (cm) : 40

Length (cm) : 60

Depth (cm) : 40

Net weight (kg) : 3.89

Gross weight (kg) : 5.40

3 700420 342120
Outer package 3


x 864

Pallet
Height (cm) : 135

Length (cm) : 120

Depth (cm) : 80

Net weight (kg) : 46.66

Gross weight (kg) : 74.75

3 700420 342434