Bi-metal CLIC II hole saw Ø 70 mm

Caracteristics

Ø : *70*
Depth of cut : *44*
Steel : *170-110*
Stainless steel : *85-55*
Recommended speed in wood and PVC : *2000-1500*

Materials

- Metal
- Wood
- Plasterboard

GENERAL INFORMATION

Description
Supplied without shaft or pilot drill.

Technical details
Material: HSS steel with 8% cobalt.
Teeth per inch: 4/6.

Advice
Do not use with hammer mode.

Application(s)
Ideally suited for steel, cast iron, aluminium (alloyed and non alloyed), non-ferrous metals, gypsum board, as well as natural and hard wood.

Instructions
1. To be fitted onto a hole saw shank CLIC II BIZ 780 150 or BIZ 780 151.

ADDITIONAL INFORMATION

Hardness: 65-67 HRC.
Diameter and speed of use on next page.

ACCESSORIES



HEX. SHAFT FOR CLIC II HOLE SAW WITH HSS PILOT DRILL 120 MM

HSS PILOT DRILL FOR CLIC II HOLE SAW 120 MM

LOGISTIC INFORMATION

Packaging

Blister package
Height (cm) : 16.6
Length (cm) : 10.5
Depth (cm) : 8.1
Net weight (kg) : 0.25
Gross weight (kg) : 0.28

3 700420 392392

Outer package 1

x 10

Carton box
Height (cm) : 23
Length (cm) : 33.2
Depth (cm) : 19.7
Net weight (kg) : 2.8
Gross weight (kg) : 2.98

3 700882 122186

Outer package 2

x 40

Carton box
Height (cm) : 40
Length (cm) : 60
Depth (cm) : 60
Net weight (kg) : 11.94
Gross weight (kg) : 13.44

3 700882 122278

Outer package 3

x 480

Pallet
Height (cm) : 135
Length (cm) : 120
Depth (cm) : 80
Net weight (kg) : 161.33
Gross weight (kg) : 184.33

3 700882 122360