Sleeve anchor hexagonal head hot dip galvanised Ø 10 x 60 mm (x 25)



Caracteristics

Ø : *10*
Length : *60*
Tensile strength : *225*
Quantity : *25*
Selling unit : *Each*

Materials

Solid materials

Benefits

- Simple and easy fitting through the object to fasten.

GENERAL INFORMATION

Technical details
C2 mechanical zinc plated.
Hexagonal head.

Application(s)
Secured fastening of heavy loads in solid materials (smooth concrete and stone).

Instructions
1. Drill the Ø indicated.
2. Clean the fastening hole.
3. Insert the sleeve anchor with a hammer.
4. Tighten with a wrench.

LOGISTIC INFORMATION

Packaging

Plastic box
Height (cm) : 13
Length (cm) : 8.7
Depth (cm) : 8.7
Net weight (kg) : 0.93
Gross weight (kg) : 1

3 700882 130303

Outer package 1

x 9

Carton box
Height (cm) : 14
Length (cm) : 27.5
Depth (cm) : 27.5
Net weight (kg) : 8.37
Gross weight (kg) : 9.25

3 700882 135209

Outer package 2

x 504

Pallet
Height (cm) : 113
Length (cm) : 113
Depth (cm) : 80
Net weight (kg) : 468.72
Gross weight (kg) : 537.78

3 700882 135353