

Bi-metal CLIC II hole saw Ø 102 mm



Characteristics

Ø : **102**

Depth of cut : **44**

Steel : **110-52**

Stainless steel : **55-40**

Recommended speed in wood and PVC : **1500-1000**

Materials

- ✓ Metal
- ✓ Wood
- ✓ Plasterboard



GENERAL INFORMATION

Description

Supplied without shaft or pilot drill.

Technical details

Material: HSS steel with 8% cobalt.

Teeth per inch: 4/6.

Advice

Do not use with hammer mode.

Application(s)

Ideally suited for steel, cast iron, aluminium (alloyed and non alloyed), non-ferrous metals, gypsum board, as well as natural and hard wood.

Instructions

1. To be fitted onto a hole saw shank CLIC II BIZ 780 150 or BIZ 780 151.



ADDITIONAL INFORMATION

Hardness: 65-67 HRC.

Diameter and speed of use on next page.



ACCESSORIES



HEX. SHAFT FOR CLIC II
HOLE SAW WITH HSS
PILOT DRILL 120 MM



HSS PILOT DRILL FOR
CLIC II HOLE SAW 120
MM


LOGISTIC INFORMATION
Packaging

Blister package
Height (cm) : 21.5

Length (cm) : 16.1

Depth (cm) : 9.5

Net weight (kg) : 0.46

Gross weight (kg) : 0.56

3 700882 171214
Outer package 1


x 4

Carton box
Height (cm) : 23

Length (cm) : 33.2

Depth (cm) : 19.7

Net weight (kg) : 2.22

Gross weight (kg) : 2.41

3 700882 171467
Outer package 2


x 16

Carton box
Height (cm) : 40

Length (cm) : 60

Depth (cm) : 40

Net weight (kg) : 9.63

Gross weight (kg) : 11.14

3 700882 172259
Outer package 3


x 192

Pallet
Height (cm) : 135

Length (cm) : 120

Depth (cm) : 80

Net weight (kg) : 133.68

Gross weight (kg) : 156.68

3 700882 172723