3 way lever push wire connector Biz'Wing 4 0.2-4 mm² (x 50)



Caracteristics

Number of inputs : *3*
Length *(mm)* **: *18.6***
Width *(mm)* **: *20.64***
Height *(mm)* **: *9.6***

Norms

> EN60998-1:2004 ; EN 60998-2-2:2004

Benefits

- It is important to strip the wires up to 11 mm.
- Ergonomic, flexible levers ensure ease of use.
- For flexible and rigid wires up to 4 mm^2.
- Transparent body for better management of connections.

Compliance marks

GENERAL INFORMATION

Technical details

Permissible cross-section for flexible wires: 0.34 to 4 mm^2.
Permissible cross-section for single and multi-stranded solid wires: 0.2 to 4 mm^2.
Glow wire resistance: 850 °C.
Maximum ambient operating temperature: 85 °C (T85).
Voltage (V): 450.
Current (A): 32.
Strip off: 11 mm.
Test points.
Material: polycarbonate.

Instructions

1. 1. Strip wires precisely up to 11 mm.
2. 2. Do not twist multi-strand wires.
3. 3. Open the levers.
4. 4. Insert the stripped wires into the bottom of the connector.
5. 5. Close the levers.

LOGISTIC INFORMATION

Packaging



Carton box
Height (cm) : 4.3
Length (cm) : 10
Depth (cm) : 8.6
Net weight (kg) : 0.23
Gross weight (kg) : 0.24

3 701395 106731

Outer package 1



x 60.00

Carton box
Height (cm) : 28.4
Length (cm) : 45
Depth (cm) : 23
Net weight (kg) : 10.92
Gross weight (kg) : 10.97

3 701395 111025

Outer package 2



x 1800.00

Pallet
Height (cm) : 120
Length (cm) : 80
Depth (cm) : 130
Net weight (kg) : 329.1
Gross weight (kg) : 344.1

3 701395 111056