RUSH

THE COMFORT OF PANORAMIC VISION

The wrap-around lightweight RUSH model offers perfect optical quality, maximum comfort and a modern design.





1652301 • Clear Lens



1652302 • Smoke Lens



1652310 • Twilight Lens



RUSHPSJ • Amber Lens

OPTIONAL

Positive Seal Gasket
Ref. 1652318





25g

- **ULTRA LIGHT WEIGHT**
- **BUILT IN BROW PROTECTION**
- **FULLY RECYCLABLE ALL POLYCARBONATE FRAME**
- **ADJUSTABLE PVC NOSE BRIDGE PLUS COMFORT BARS IN THE TEMPLE ARMS.**

bollé SAFETY

RUSH

THE COMFORT OF PANORAMIC VISION

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
RUSH	Clear	1652301	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	Smoke	1652302	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	Twilight	1652310	I1	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	Amber	RUSHPSJ	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog

LENS MARKING

I. The letter 'I' signifies 'Medium Impact' approval.

O. The letter 'O' signifies that the product has been approved for the use both outdoors and indoors, and the terminology used by Australian standards is 'outdoor un–tinted'. This marking appears on all clear, amber and contrast lenses.

OCULAR LENS CATEGORY:

O. Range of luminous transmittance 80-100% (clear, amber).

1 . Range of luminous transmittance 43 -88% (twilight).

3 . Range of luminous transmittance 8 -18% (smoke).

APPLICATIONS

- Assembly and production work
- Process work
- Emergency response
- Driving
- Solar UV exposure
- Laboratory
- Dental

MAIN MARKETS

- Manufacturing
- Petrochemical
- Construction
- Government
- Mining
- Medical and dental
- Food industry

LENSES

- 2mm polycarbonate
- 9 base curve
- 'ALS' anti-fog/anti-scratch coating on both sides of lens: Clear, Smoke, Twilight and Amber
- 99.9% UV 385 – Clear
- 99.9% UV 400 – Smoke, Twilight, Amber

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B–clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 9
FRAME	PC + PVC
STRAP	Non Applicable
FOAM	Non Applicable
SPARE LENSES	No

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

08/03/2019

ASIA/PACIFIC HEADQUARTERS:
Bollé Safety AU Pty Limited
32–40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

bollesafety.com.au

NEW ZEALAND:
T.: 0800 2655 369
E: bolle@bolle.co.nz

bollé SAFETY