

24V MEANWELL POWER SUPPLIES | IP67



CODE	OUTPUT WATTS	SYSTEM WATTS	OUTPUT AMPS	POWER FACTOR	AC INRUSH CURRENT	DIMENSIONS	WEIGHT
BL-PS-IP-XLG150-24-A	150W	150W	6.25A	0.95	50A peak @ 230V	W63 × H35.5 × L180mm	0.8kg
BL-PS-IP-XLG200-24-A	199W	200W	8.3A	0.95	50A peak @ 230V	W63 × H35.5 × L199mm	0.85kg
BL-PS-IP-XLG320-24-VA	312W	320W	13A	0.92	50A peak @ 230V	W77 × H39.5 × L246mm	1.45kg

INPUT VOLTS	150/200W: 100–240V AC 320W: 120–277V AC	LIFETIME	>50,000hrs	INGRESS PROTECTION	IP67
OPERATING TEMP.	–40°C ~ +85°C	WARRANTY	5 years	ADJ. FUNCTION	312W Only: Output voltage 12/24V adjustable via built-in potentiometer <i>24V as default</i>
DISTANCE FROM INSTALLATION (Secondary Output)	Recommended under 10 metres	COMPLIANCE		ELECTRICAL PROTECTION	Overload, short circuit, overheat, and automatic re-start
				MATERIAL	Metal case
				CONNECTION METHOD	<i>Input</i> 270mm 3 core double insulated flex <i>Output</i> 270mm 2 core double insulated flex
				CONTROL	Dimmable on the secondary output only by PWM