

1025USBC-BB

Double switched socket + USB charger, Clipsal Solis T Series, horizontal, USB C type, 10A, brushed brass



Launching in : SEP 2025

ⓘ Coming soon

Main

Product or component type	Switched socket with USB charger
Device presentation	Complete product
Standards	AS/NZS 3112
Product certifications	RCM
Main colour tint	Brushed brass

Complementary

Range	Clipsal Solis T Series
Socket number	2
Device mounting	Wall mounted 65 mm
Cover type	With shutter
Number of power socket outlets	2 x 2P + E, Australian/New Zealand
Rated current	10 A 230/240 V, AC, 50 Hz
Connections - terminals	4 x 2.5 mm ² screw terminals 3 x 4 mm ² screw terminals
Colour tint	Brushed brass
Surface finish	Aluminium
Surface treatment	Anodised
Connector type	USB type C
Material	Aluminium
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Wire stripping length	16 Mm
Fixing mode	By screws
Fixing center	120 mm
Height	74 Mm
Width	148 Mm
Depth	68.9 Mm
Sale per indivisible quantity	1
Device mounting	Flush
Installation direction	Horizontal
Control type	Rocker
Thickness	3.9 Mm

Cut-out dimensions	130 x 50 mm
Number of rocker	2

Environment

Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.5 Cm
Package 1 Width	8 Cm
Package 1 Length	8 Cm
Package 1 Weight	252 G
Unit Type of Package 2	CAR
Number of Units in Package 2	30
Package 2 Height	32.5 Cm
Package 2 Width	25 Cm
Package 2 Length	41 Cm
Package 2 Weight	7.94 Kg

Offer Sustainability

Total lifecycle Carbon footprint	2 kg CO2 eq.
Carbon footprint of the manufacturing-phase [A1 to A3]	0.6530701171907696
Carbon footprint of the manufacturing-phase [A1 to A3]	0.7 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.9495021530324987
Carbon footprint of the distribution phase [A4]	0.9 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.0036124433850897412
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.4193009966013595
Carbon footprint of the use phase [B2, B3, B4, B6]	0.4 kg CO2 eq.
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
RoHS exemption information	 Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.29450699568807825
Carbon footprint of the end-of-life phase [C1 to C4]	0.3 kg CO2 eq.
Environmental Disclosure	 Product Environmental Profile
Total lifecycle Carbon footprint	2
EU RoHS Directive	Compliant  EU RoHS Declaration
REACH Regulation	 REACH Declaration
End of life manual availability	No need of specific recycling operations
Take-back	No

Product Life Status : **Precommercialisation**