Product data sheet
Characteristics

30MOS-WE
30MOS 1 WAY / 2 WAY MECHANISM - OUTSIDE

Main

Range of product	Standard Series Series 30
Product brand	Clipsal
Device presentation	Basic element

Complementary

Switch function	2-way
Actuator	Rocker
Number of rocker	1
Device mounting	Flush
Local signalling	without
[Ue] rated operational voltage	250 V AC
Rated current	10 A
Marking	Outside
Marking location	Marking on surface

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	13.7 g
Package 1 Height	22 mm
Package 1 width	22 mm
Package 1 Length	30 mm
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	0.078 kg
Package 2 Height	36 mm
Package 2 width	54 mm
Package 2 Length	74 mm
Unit Type of Package 3	CAR
Number of Units in Package 3	500
Package 3 Weight	8 kg
Package 3 Height	226 mm
Package 3 width	191 mm
Package 3 Length	359 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile