

Product data sheet

Characteristics

755PFM4

Photoelectric Smoke Alarm FireTek - Flush mount - 240 V mains-powered - 9V battery backup



Main

Range	Fire Tek
Product brand	Clipsal
Product or component type	Smoke detector
Device application	Early detection of smouldering fires and open fires
Electronic sensor type	Photo-electric sensor
Colour	White (RAL 9003)
Quantity per set	Set of 1
Type of packing	Carton

Complementary

Supply	Mains
[Us] rated supply voltage	220...240 V AC 50 Hz
Backup type	Battery
Battery type	Alkaline 9 V 6LR61
Battery life	1 year(s)
[In] rated current	13 mA: 9 V DC not in operation 40 mA: 9 V DC operation
Output voltage limits	Interconnection: 6.5...20 V
Type of alarms	Low battery at 6.9...7.5 V
Detection type	Smoke
Device composition	1 smoke detector 1 mounting base 1 dust protection foil 1 user guide 3 screws 1 sticker sheet
Function available	Local alarm Hush function Self-test of smoke detection
Technology type	Scattered light (Tyndall effect)
Type of measurement	Optic
Maximum number of device interconnected	40 for wired alarm wired over <= 150 m
Horn level	85 dB at 3 m, minimum
Local signalling	Sound: signal Visual: LED (red) for warning and low battery Visual: LED (green) for ON status
Connections - terminals	Screw terminal (line) - 2 x 1...3 x 2.5 mm ² Screw terminal (neutral) - 2 x 1...3 x 2.5 mm ² Screw terminal (earth loop) - 2 x 1...3 x 2.5 mm ² Screw terminal (interconnect) - 2 x 1...3 x 2.5 mm ²
Material	PC (polycarbonate)
Type of installation	Indoor
Device mounting	Flush
Mounting support	Ceiling

Fixing mode	By screws
Diameter	108 mm
Depth	102.6 mm
Projecting depth	23 mm
Net weight	263 g

Environment

IP degree of protection	IP20
Ambient air temperature for operation	0...45 °C
Relative humidity	5...95 %
Product certifications	RCM SAI Activfire
Standards	ISO 8201 AS 3786:2014 AS/NZS 60950.1 AS/NZS 60065

Packing Units

Package 1 Weight	257.000 g
Package 1 Height	106.000 mm
Package 1 width	145.000 mm
Package 1 Length	145.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information