


Product data sheet

Specifications



Grid Switched Socket + Switch, Iconic, 10A Horizontal 250V

PDL394XUA-VW

Main

Range	PDL Iconic
Product or component type	Switched socket
Device presentation	Complete product
Number of Switched socket	1
Colour tint	Vivid white
Connections - terminals	Screw terminals

Complementary

Installation direction	Horizontal
Device mounting	Flush
Number of Switch	1
Rated current	10 A
[Ue] rated operational voltage	230/240 V
Outlet poles configuration	2P + E
fixing mode	By screws
Material	PC (polycarbonate)
Clamping connection capacity	1 x 2.5...4 x 2.5 mm ² for rigid cable(s) 1 x 2.5...4 x 2.5 mm ² for stranded cable(s) 1 x 2.5...4 x 2.5 mm ² for flexible cable(s)
Surface finish	Matt
surface treatment	Untreated
Wire stripping length	16 mm
Product weight	100 g

Environment

Ambient air temperature for operation	0...45 °C
---------------------------------------	-----------

Dimensions

Height	78 mm
Width	120 mm
Depth	31 mm

Packing Units

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.7 cm
Package 1 Width	7.8 cm
Package 1 Length	8.4 cm
Package 1 Weight	84 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	8 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.7 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	7 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Halogen free product
PVC free	No
Silicone-free	No

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	43
End of life manual availability	No need of specific recycling operations
Take-back	No

Offer Marketing Illustration

Product benefits / Features

Technical Benefits
Iconic

