

Delta DC 25 kW Electric Vehicle Charger Wallbox Type 7 m CCS2 and CHAdeMO

- CCS / CHAdeMO dual charging ports
- Max. 94% power efficiency
- RFID card reader for user authentication
- Network connectivity (OCPP 1.5S and 1.6J)
- IP55 protection and IK10 vandal-proof casing
- Applications : Highway Service , Parking Lot , Service Station , Commercial Building , Fleet

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type Electric Vehicle Charging	DC Chargers
Height	680 mm
Width	430 mm
Depth	230 mm
Weight	47 kg
Wireless Technology	3G Wi-Fi
Efficiency, Electrical, Full load	94 >=%
Operating Temperature, Min	-30 °C min
Operating Temperature, Max	50 °C max
Storage Temperature, Min	-40 °C min
Storage Temperature, Max	85 °C max
CE Marked	Yes
Input Current, Max	50 A max
Output Current, Max	60 A max
Input Voltage, 3ph, max (rms)	415 V AC max (rms)
Connector(s), Vehicle	CCS2 vehicle CHAdeMO
IK Rating	IK10
IP Rating	IP55

Catalogue No: **EVDE25D7DUM**

DELTA DC 25kW EV CHARGER WALLBOX TYPE 7M CCS2 & CHAdeMO

Electric Vehicle Charging Equipment > DC Chargers > DC Chargers up to 25 kW > 25 kW DC Wallbox > Delta DC Wallbox Features



REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-