Specifications







Eaton XTOM2P4AC1

Eaton XT IEC control relay, XT IEC Miniature Overload Relay, 1.6-2.4A overload range, 45 mm - mini Frame size, 1NO-1NC contact configuration, Direct to contactor mounting, 10A trip type

General specifications	
PRODUCT NAME	Eaton XT IEC control relay
CATALOG NUMBER	XTOM2P4AC1
EAN	4015080144793
PRODUCT LENGTH/DEPTH	2.75 in
PRODUCT HEIGHT	2 in
PRODUCT WIDTH	3 in
PRODUCT WEIGHT	0.7 lb
COMPLIANCES	CE Marked ATEX Compliant RoHS Compliant
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
CATALOG NOTES	Observe the maximum permissible fuse of the contactor with direct device mounting. Clearance of at least 5 mm is required between the overload relays when fitted firectly to contactor.

Powering Business Worldwide

Product specifications

OVERLOAD RANGE	1.6-2.4A
TYPE	Control relay
FRAME SIZE	45 mm - mini
CONTACT CONFIGURATION	1 NO, 1 NC
MOUNTING METHOD	Direct
TRIP TYPE	10 A

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTOM2P4AC1

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.